Calla Ruffled Glass Wall Light

Installation Guide

In the box

1 x ruffled glass shade · 1 x wall mount with two lampholders · shade screws · terminal block · screws and wall plugs

You will need

Drill, screwdriver, pencil and spirit level. Two SES (E14) globes, sold separately (warm white LED, 2700 to 3000K, recommended). Suggested height: centre about 120 to 140 cm from the floor beside a bed, 150 to 170 cm in a living room or hallway.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Glass is fragile: keep the shade safely aside until the last step.
- Use LED globes and do not exceed the maximum wattage shown on the lampholders.

Step by step

1. **Connect the wiring**
   With the power OFF, connect the supply to the light through the terminal block: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
2. **Fix the wall mount**
   Hold the mount flat against the wall, check it is level and mark the three holes. Drill, insert the wall plugs and screw the mount firmly to the wall, with the wires tucked behind it.
3. **Fit the globes**
   Screw an SES (E14) globe into each lampholder, gently and without force.
4. **Fit the glass shade**
   Hold the shade over the mount, fix it with the two screws at its top corners, then fit the small screw underneath. Tighten by hand only.
5. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the glass with a soft, dry cloth, or clean it with a little mild glass cleaner on a cloth. Never wet the lampholders.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.