Fleur Scalloped Glass Semi-Flush Ceiling Light

Installation Guide

In the box

1 x scalloped glass shade · 1 x brass-finish mount and canopy (10 cm) with lampholder · mounting bracket · fixing hardware

You will need

Drill, screwdriver, pencil and stepladder. One ES (E27) globe, sold separately (warm white LED, 2700 to 3000K, recommended).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Glass is fragile: unpack and handle the shade with care.

Step by step

1. **Fix the bracket**
   Separate the canopy from its bracket. Mark the holes and fix the bracket firmly to the ceiling, into a joist or with suitable plasterboard anchors.
2. **Connect the wiring**
   With the power OFF, connect the light to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
3. **Fit the mount**
   Tuck the wires neatly inside, then fit the brass-finish canopy over the bracket and secure it flush with the ceiling.
4. **Fit the globe**
   Screw an ES (E27) globe into the lampholder, gently and without force.
5. **Fit the glass shade**
   Fit the glass shade onto the mount and secure it by hand until it is held firmly. Do not over-tighten.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Wipe the glass with a soft, dry or slightly damp cloth. Never wet the lampholder or the cable, and avoid abrasive cleaners.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.