Hartley Black Wagon Wheel Chandelier

Installation Guide



In the box

Ø80 cm ring with 12 candle holders · 4 rods · 3 chains (30, 51, 99 cm) · canopy and mounting plate · 12 E14 LED globes · screws

You will need

Drill, screwdrivers, stepladder and two people. Height adjusts from 76 to 249 cm; over a table, hang the ring 75 to 85 cm above the top.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Fix only into a joist or a fixing rated for the chandelier's weight.

Step by step

1. **Fix the mounting plate**
   Mark the holes, drill and tap in the wall plugs (skip the plugs on timber), then screw the plate to the ceiling with the supply cable through the centre.
2. **Set the height**
   Choose the chain length, join it with the screw links and weave the cable through the chain.
3. **Hang the ring**
   Attach the 4 rods to the ring and hub, then hook the chain to the canopy and check the ring is level.
4. **Connect the wiring**
   With the power OFF at the switchboard: Active to L, Neutral to N, Earth to the earth terminal. Check every connection is tight and insulated.
5. **Fit the canopy and globes**
   Slide the canopy up and screw it to the plate until flush, then screw an E14 LED candle globe into each of the 12 holders.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the ring and candle sleeves with a soft, dry cloth. Never use water or solvents on the painted iron.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.