Hollis Gooseneck Barn Wall Light

Installation Guide

In the box

1 x gooseneck arm with barn shade (Ø 24 cm) and ES (E27) lampholder · round wall plate (Ø 12 cm) with mounting bracket · fixing hardware

You will need

Drill, screwdriver, wire strippers, pencil, spirit level and stepladder. One ES (E27) globe, sold separately (a warm white LED filament globe, 2700 to 3000K, suits the look).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- The light projects 37 cm from the wall: check that doors and windows can open freely before you drill.
- Fix the bracket into a stud, masonry or another solid support with suitable fixings.

Step by step

1. **Power off**
   Switch off the circuit at the switchboard before starting.
2. **Fix the bracket**
   Separate the wall plate from its bracket. Mark the holes with a spirit level, then screw the bracket firmly to the wall.
3. **Connect the wiring**
   Connect the light to the supply: Active to L, Neutral to N, and Earth to the earth terminal.
4. **Fit the wall plate**
   Tuck the wires neatly inside, then fit the wall plate over the bracket and tighten the side screws.
5. **Fit the globe and test**
   Screw an ES (E27) globe into the lampholder, then restore the power and switch on.

Care and cleaning

Switch off and let the globe cool first. Wipe the metal with a soft, dry cloth and avoid harsh cleaners, which can damage the aged finish.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.