Ishi Wabi-Sabi Pebble Pendant Light



Installation Guide

In the box

1 x textured pebble shade with lampholder · 1 x ceiling canopy (Ø 10 cm) with bracket · adjustable cable (up to 150 cm) · fixing hardware

You will need

Drill, screwdriver, pencil, stepladder. One ES (E27) globe, sold separately: max. 60 W, or LED up to 12 W (warm white 2700-3000K suggested; dimmable globe + compatible dimmer to dim). Hang about 75 cm above a table or bench.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).

Step by step

1. **Mark and drill**
   Hold the ceiling plate in place and mark the holes with a pencil. Drill the holes and tap in plastic anchors, or fix into a joist.
2. **Fix the ceiling plate**
   Line up the plate with the anchors and tighten the screws so it sits firmly against the ceiling.
3. **Connect the wiring**
   With the power OFF, connect the pendant cable to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
4. **Fit the canopy**
   Push the canopy up over the plate, tuck the wires neatly inside and secure it with the side screws so it sits flush with the ceiling.
5. **Set the drop**
   Slide the cable through the grip on the canopy to the height you want (up to 150 cm). Your electrician can trim any extra.
6. **Fit the globe and test**
   Screw an ES (E27) globe (max. 60 W, LED up to 12 W) into the lampholder, gently. Restore the power at the switchboard and switch on.

Care and cleaning

Turn the light off and let it cool. Dust the shade with a soft, dry brush or cloth. Do not use water or cleaning sprays on the textured finish.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.