Jasper Woodgrain & Amber Glass Pendant Light

Installation Guide

In the box

1 x amber glass shade with woodgrain-finish fitting and lampholder · 1 x ceiling canopy with mounting bracket · adjustable suspension cable · fixing hardware

You will need

Drill, screwdriver, pencil and stepladder. One ES (E27) globe, sold separately (warm white LED, 2700 to 3000K, recommended). Hang the shade about 75 cm above a table or bench (70 to 80 cm over an island).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Dimming needs a dimmable E27 LED globe and a compatible wall dimmer, fitted by your electrician.
- Glass is fragile: unpack and handle the shade with care.

Step by step

1. **Fix the mounting bracket**
   Separate the canopy from its bracket. Mark the holes and fix the bracket firmly to the ceiling, into a joist or with suitable plasterboard anchors.
2. **Set the drop**
   Adjust the suspension cable to the drop you want and lock it in place. Your electrician can trim any extra cable.
3. **Connect the wiring**
   With the power OFF, connect the pendant cable to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
4. **Fit the canopy**
   Push the canopy up over the bracket, tuck the wires neatly inside and secure it so it sits flush with the ceiling.
5. **Fit the globe**
   Screw an ES (E27) globe into the lampholder inside the shade, gently and without force.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Wipe the glass with a soft, dry or slightly damp cloth. Never wet the lampholder or the cable, and avoid abrasive cleaners.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.