Juniper Linear Glass Globe Chandelier

Installation Guide



In the box

Linear frame · glass globes (9 or 11) · G9 LED globes · suspension rod and support wire · ceiling canopy with mounting plate · screws and wall plugs

You will need

Drill, screwdrivers, stepladder and two people. The drop adjusts up to 100 cm; over a table or island, hang the lowest globe about 75 to 85 cm above the top.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Fix only into a joist or a fixing rated for the chandelier's weight. Fit the glass globes last.

Step by step

1. **Fix the mounting plate**
   Mark the holes, drill and tap in the wall plugs (skip the plugs on timber), then screw the plate to the ceiling with the supply cable through the centre.
2. **Hang the frame**
   With a helper, hang the frame from the rod and the support wire, then set the drop and check the bar is level.
3. **Connect the wiring**
   With the power OFF at the switchboard: Active to L, Neutral to N, Earth to the earth terminal. Check every connection is tight and insulated.
4. **Fit the canopy**
   Tuck the wires in and screw the canopy to the mounting plate until it sits flush.
5. **Fit globes and glass**
   Push a G9 LED globe into each holder, then screw each glass globe on by hand until snug.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the frame with a soft, dry cloth. Wash the glass globes in warm soapy water and dry fully before refitting.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.