Juno Saucer LED Pendant Light

Installation Guide



In the box

1 x saucer light with integrated LED · 1 x ceiling canopy with mounting bracket · adjustable cable · screws and wall plugs

You will need

Drill, screwdriver, pencil and stepladder. No globe needed: the LED is built in. Hang the saucer about 75 cm above a table or bench (70 to 80 cm over an island).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Use the wall switch to change between warm, neutral and cool white.
- Indoor use in dry areas only.

Step by step

1. **Check the balance first**
   Hold the light up by its cable. If the saucer leans, hold the ball in one hand and gently press the saucer the other way, a little at a time, until it hangs level. A slight tilt from transport is normal.
2. **Fix the mounting bracket**
   Separate the canopy from its bracket and fix the bracket firmly to the ceiling, into a joist or with plasterboard anchors.
3. **Set the drop**
   Loosen the cable grip at the canopy, set the drop (up to 120 cm) and tighten the grip. Your electrician can trim extra cable.
4. **Connect the wiring**
   With the power OFF, connect the cable to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
5. **Fit the canopy**
   Push the canopy up over the bracket, tuck the wires neatly inside and tighten the screws until it sits flush with the ceiling.
6. **Test**
   Restore the power, switch on and check the saucer hangs level. If needed, adjust it again with the light off.

Care and cleaning

Turn the light off. Dust the saucer, ball and diffuser with a soft, dry cloth. Do not use solvents or abrasive cleaners, which can mark the acrylic.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.