Kirra Arched Glass Globe Chandelier

Installation Guide



In the box

Frame with arched arms · 6 x opal glass globes · 6 x G9 LED globes (5 W) · ceiling canopy with mounting bracket · screws

You will need

Drill, screwdrivers, stepladder and two people. Height is 62 cm from canopy to lowest globe; hang that globe about 75 cm above a table.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Fix only into a joist or a fixing rated for the chandelier's weight. Fit the glass globes last.

Step by step

1. **Assemble the arms**
   On a soft blanket, screw each arched arm to the stem collar and to the hub at its base.
2. **Join the arm wires**
   In the hub, join each arm's wires to the main cable (L to L, N to N), then screw on the hub cover.
3. **Fix the mounting bracket**
   Screw the bracket into a joist or rated fixing, with the supply cable through the centre.
4. **Connect the wiring**
   With a helper and the power OFF, use the terminal block: Active to L, Neutral to N, Earth if fitted.
5. **Fit the canopy**
   Tuck the wires in and tighten the two side screws until the canopy sits flush.
6. **Fit the globes**
   Push a G9 LED globe into each holder, then screw on the glass globes as pictured.
7. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the frame and glass with a soft, dry cloth. Wash the glass globes in warm soapy water and dry fully before refitting.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.