Maris Pleated Fabric Chandelier Pendant Light

Installation Guide



In the box

Pleated fabric shade on iron frame with lampholders · metal chains · ceiling canopy with hook and bracket · terminal block · fixings

You will need

Drill, screwdriver, pencil and stepladder. ES (E27) globes, one per lampholder, sold separately (warm white LED recommended). Hang the shade about 75 cm above a table or bench.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Use LED globes only and do not exceed the maximum wattage shown on the lampholders.
- Fix to a joist or suitable anchors, and have a helper hold the shade.

Step by step

1. **Fix the mounting bracket**
   Separate the canopy from its bracket and fix the bracket to the ceiling with two screws, into a joist or with suitable anchors.
2. **Attach the chains and globes**
   Lay the shade upside down on a soft surface. Hook the chains onto the frame, evenly spaced, and screw an ES (E27) globe into each lampholder.
3. **Hang the light**
   Hook the top of the chain under the canopy, set the drop (up to 120 cm) and check the shade hangs level.
4. **Connect the wiring**
   With the power OFF, connect the cable through the terminal block: Active to L, Neutral to N, and Earth to the earth terminal if fitted.
5. **Fit the canopy**
   Tuck the wires in, push the canopy over the two bracket screws and secure it with the two decorative nuts.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the pleated fabric with a soft, dry brush. Do not wet the fabric.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.