Nordic Glass Globe Ceiling Light

Installation Guide



In the box

1 x glass globe with inner shade · 1 x metal canopy with lampholder and mounting bracket · 12 cm rod (semi-flush only) · fixings

You will need

Drill, screwdriver, pencil and stepladder. One ES (E27) globe, sold separately (warm white LED, 2700 to 3000K, recommended).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Glass is fragile: handle the globe and inner shade with care.
- Use an LED globe and do not exceed the maximum wattage shown on the lampholder.

Step by step

1. **Fix the mounting bracket**
   Separate the canopy from its bracket. Mark the holes and fix the bracket firmly to the ceiling, into a joist or with suitable plasterboard anchors.
2. **Connect the wiring**
   With the power OFF, connect the light to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
3. **Fit the canopy**
   Semi-flush: first fit the 12 cm rod as shown. Push the canopy up over the bracket, tuck the wires inside and secure it flush with the ceiling.
4. **Fit the globe**
   Screw an ES (E27) globe into the lampholder, gently and without force.
5. **Fit the glass**
   Fit the inner shade, then the outer glass globe, using the fittings provided. Tighten gently by hand.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Wipe the glass with a soft, dry cloth. Do not use water near the lampholder or abrasive cleaners.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.