Pike Black LED Tube Pendant Light

Installation Guide



In the box

1 or 2 black aluminium tubes with integrated LED · ceiling canopy with mounting bracket (Ø 6 cm single, Ø 15 cm double) · 200 cm adjustable cable(s) · screws and wall plugs

You will need

Drill, screwdriver, pencil and stepladder. No globe needed: the LED is built in. Hang about 75 cm above a bench or table (70 to 80 cm over an island); beside a bed, set it to suit your reading position.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Double head: both tubes share one canopy; set the drop of each cable.
- Indoor use in dry areas only.

Step by step

1. **Fix the mounting bracket**
   Separate the canopy from its bracket. Mark the holes and fix the bracket firmly to the ceiling, into a joist or with suitable plasterboard anchors.
2. **Set the drop**
   Loosen the cable grip at the canopy, set the drop you want, up to 200 cm, and tighten the grip. Your electrician can trim any extra cable.
3. **Connect the wiring**
   With the power OFF, connect the cable(s) to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
4. **Fit the canopy**
   Push the canopy up over the bracket, tuck the wires neatly inside and tighten the screws until it sits flush with the ceiling.
5. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off. Dust the tube with a soft, dry cloth. Do not use water, solvents or abrasive cleaners.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.