Pippa Ribbed Glass Globe Wall Light

Installation Guide

In the box

1 x brushed brass curved arm with round wall plate (Ø 8 cm) and SES (E14) lampholder · ribbed glass globe (Ø 15 cm) · mounting bracket · fixing hardware

You will need

Drill, screwdriver, wire strippers, pencil, spirit level and stepladder. One SES (E14) globe, sold separately (a warm white LED globe, 2700 to 3000K, suits the coloured glass).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- The light projects 22.7 cm from the wall: beside a bed, allow room for your head and pillows.
- Handle the glass globe with care and keep it aside, wrapped, until the last step.

Step by step

1. **Power off**
   Switch off the circuit at the switchboard before starting.
2. **Fix the bracket**
   Separate the wall plate from its bracket. Mark the holes with a spirit level, then screw the bracket firmly to the wall.
3. **Connect the wiring**
   Connect the light to the supply: Active to L, Neutral to N, and Earth to the earth terminal.
4. **Fit the wall plate**
   Tuck the wires neatly inside, then fit the wall plate over the bracket and tighten the screws.
5. **Fit the globe and glass, then test**
   Screw an SES (E14) globe into the lampholder, fit the glass globe onto the arm, then restore the power and switch on.

Care and cleaning

Switch off and let the globe cool first. Clean the glass with a soft cloth and a mild glass cleaner; wipe the brass with a dry cloth.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.