Tarra Travertine & Wood Wall Light

Installation Guide



In the box

1 x travertine tube on wooden wall plate · G9 warm white (3000K) LED globe · 1 x mounting bracket · screws and wall plugs

You will need

Drill, screwdriver, pencil and spirit level. The G9 LED globe is included. Suggested height: centre about 120 to 140 cm from the floor beside a bed, 150 to 170 cm in a living room or hallway.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Indoor, dry areas only.
- Natural travertine is fragile: handle the tube with care and never over-tighten the screws.

Step by step

1. **Remove the mounting bracket**
   Undo the screws on the back of the light and lift off the mounting bracket. Keep the screws.
2. **Fix the bracket**
   Hold the bracket in place, check it is level and mark the holes. Drill, insert the wall plugs and screw the bracket firmly to the wall, with the supply cable through the centre.
3. **Connect the wiring**
   With the power OFF, connect the light using the connector supplied to the supply: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted. Tuck the wires neatly behind the backplate.
4. **Fit the wall plate**
   Place the wall plate over the bracket and tighten the screws until it sits firmly against the wall.
5. **Fit the globe**
   Push the supplied G9 LED globe into the lampholder, gently and without force. Refit any part removed to reach it.
6. **Test**
   Restore the power at the switchboard and switch on the light.

Care and cleaning

Turn the light off and let it cool. Dust the stone and wood with a soft, dry cloth. Do not use water, chemical solvents or abrasive cleaners on the stone.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.