Tense Fabric LED Pendant Light

Installation Guide



In the box

1 x fabric shade · frame rods · LED module with suspension cable · ceiling canopy with mounting bracket · terminal block · screws and wall plugs

You will need

Drill, screwdriver, pencil and stepladder. A helper for the larger sizes. No globe needed: the LED is built in. Hang the shade about 75 cm above a table or bench (70 to 80 cm over an island).

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- The fabric shade is light and delicate: handle it gently and keep it clear of sharp edges.
- Check the ceiling position and clearance for your chosen size before fixing the bracket.

Step by step

1. **Build the frame**
   Push the frame rods together to form the ring, then slide it into the hem around the edge of the fabric shade.
2. **Fit the LED module**
   Hook the LED module and its suspension into the clips at the top of the frame, so the shade hangs evenly from it.
3. **Fix the mounting bracket**
   Screw the bracket to the ceiling, into a joist or with suitable plasterboard anchors, with the supply cable through the centre.
4. **Connect the wiring**
   With the power OFF, use the terminal block: Active to L, Neutral to N, and Earth to the earth terminal if one is fitted.
5. **Fit the canopy**
   Set the drop, tuck the wires inside, push the canopy over the bracket and tighten the two side screws.
6. **Test**
   Restore the power at the switchboard, switch on and check the shade hangs level.

Care and cleaning

Turn the light off and let it cool. Dust the fabric shade gently with a soft, dry brush or a vacuum on low with a brush head. Do not use water or cleaning sprays.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.