Tessa Linear LED Pendant Light

Installation Guide

In the box

1 x linear bar with integrated LED heads (75, 125 or 153 cm) · ceiling canopy with driver · hanging cables (up to 120 cm, adjustable) with ceiling anchors · fixing hardware

You will need

Drill, screwdriver, wire strippers, pencil, measuring tape, spirit level and stepladder. No globes needed: the LEDs are built in.

Important safety information

- This light must be installed by a licensed electrician, in line with AS/NZS 3000 (Wiring Rules) and local regulations.
- Turn the power off at the switchboard before installing, cleaning or servicing the light.
- Use screws and wall plugs suited to your wall (plasterboard, timber or masonry).
- Mark the canopy and cable anchor points along one straight line, spaced to match the cables on the bar.
- Over a dining table or kitchen island, hang the bar about 75 to 85 cm above the surface.

Step by step

1. **Power off**
   Switch off the circuit at the switchboard before starting.
2. **Mark and fix**
   Mark the canopy and anchor positions on the ceiling with a measuring tape and spirit level, then screw the canopy bracket and cable anchors firmly in place.
3. **Connect the wiring**
   Connect the light to the supply: Active to L, Neutral to N, and Earth to the earth terminal. Tuck the wires inside and fit the canopy.
4. **Set the height**
   Hang the bar on its cables and adjust each cable until the bar sits level at the height you want. Trim or coil any spare cable neatly.
5. **Test and choose the light colour**
   Restore the power and switch on. Switch off and on again to move between warm, neutral and cool white.

Care and cleaning

Switch off first. Dust the bar and heads with a soft, dry cloth; avoid water and harsh cleaners on the metal finish.

Need help?

Email hello@aussielights.com with your order number and a photo. Your light is covered by our 2-year warranty and 30-day returns.